

Melia 18 x 36 DuraFusion

















18 x	36	
COLUMN TO SERVICE	ACCOUNT OF THE	
1000	No. of Concession, Name of Street, or other Persons, Name of Street, or ot	ħ


Dimension	ns mm	Dimensions in.		
60 x 457 x 914		2 3/8 x 18 x 36		
58 kg		129 lb		
0.37 m ²		4.5 ft ²		
0.84 m ²		9.0 ft ²		
8.36 m ²	10 Rows	90.0 ft ²		
20 units		20 units		
1167 kg		2573 lb		
	60 x 457 x 58 kg 0.37 m ² 0.84 m ² 8.36 m ² 20 units	58 kg 0.37 m ² 0.84 m ² 8.36 m² 10 Rows 20 units		

Dune		
Dura	Fusion	
127002108 Oasi	s 😽	
127002109 Mark	bella 😽	
Production location	n Metcalfe	


Laying Patterns











Checkerboard

Running Bond

Offset 1/3

Herringbone

Parquet

• Techniseal 1 bag of sand covers approx. 373 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melia 18 x 36 DuraFusion Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

 $^{^{\}star}$ Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this Slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).

