

Leno Capping



smooth



textured




Bullnose



	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
Qty/cube	24 units	2 Rows
Weight/cube	925 kg	2038 lb

Code	Colour
Standard	
121000134	Range Amber Beige
10502415	Range Shaded Grey
10502416	Range Scandina Grey
10502414	Rockland Black
Cannot be double stacked	
Production location Cambridge	

Typical Row



Straight


New



	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
Qty/cube	24 units	2 Rows
Weight/cube	925 kg	2038 lb

Code	Colour
Standard	
121000141	Range Amber Beige
121000139	Range Scandina Grey
121000138	Rockland Black
Cannot be double stacked	
Production location Cambridge	

Typical Row



Lafitt


New



	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
Qty/cube	24 units	2 Rows
Weight/cube	925 kg	2038 lb

Code	Colour
Standard	
121000137	Range Margaux Beige
121000136	Range Newport Grey
121000135	Rockland Black
Cannot be double stacked	
Production location Cambridge	

Typical Row



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Leno Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm