


Melville® 60 and Melville® 60 DuraFusion Slabs




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row	
	A	60 x 190 x 380	2 3/8 x 7 1/2 x 15	DuraFusion 12051953 Marbella (2) 12051954 Silverstone (2) 12051955 Hickory (2)		
	B	60 x 380 x 380	2 3/8 x 15 x 15			
	C	60 x 380 x 570	2 3/8 x 15 x 22 7/16			
	Weight/unit (avg.)	19 kg	42 lb	Prestige 12053046 Range Amber Beige (1) 12052734 Range Margaux Beige (1) 12052104 Range Chambord Grey (1) 12052365 Range Scandina Grey (1)		
	Unit/area (avg.)	0.14 unit/m ²	1.46 units/ft ²			
	Area/layer	1.08 m ²	11.66 ft ²			
	Area/cube	10.80 m²	10 Rows	116.60 ft²		
	Qty/cube	80 units	80 units			
	Weight/cube	1538 kg	3391 lb			
	Standard 12053045 Range Shaded Grey (1) 12052733 Range Newport Grey (1)					
Sold in full cubes only Can be double stacked Production: Cambridge (1) DuraFusion - Metcalfe (2)						

Laying Patterns



Modular



Linear

1 bag of sand covers approx. 155 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.