


Melville® 80 Small Rectangle Paver




	Dimensions mm	Dimensions in.
	80 x 190 x 380	3 1/8 x 7 1/2 x 15
Weight/unit	14 kg	30 lb
Unit/area	13.89 units/m ²	1.29 units/ft ²
Area/layer	0.87 m ²	9.33 ft ²
Area/cube	7.83 m²	9 Rows 83.97 ft²
Length/layer	4.57 lin. m	15.00 lin. ft
Length/cube	41.15 lin. m	135.00 lin. ft
Qty/cube	108 units	108 units
Weight/cube	1465 kg	3225 lb


Code	Colour
Prestige	
10550871	Range Amber Beige
10551033	Rockland Black
10551031	Range Scandina Grey
Standard	
10550870	Range Shaded Grey

Sold in full cubes only
Production location Cambridge


Typical Row



Laying Patterns



Linear



Herringbone

1 bag of sand covers approx. 77 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.