



Urbano® Wall



		Dimensions mm	Dimensions in.	Code	Colour	Typical Row																		
A	A	120 x 201 x 335	4 3/4 x 7 15/16 x 13 3/16		Standard	<table border="1"> <tr><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td></tr> <tr><td>B</td><td>A</td><td>C</td></tr> <tr><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td></tr> </table>							B	A	C									
B	A	C																						
	B	120 x 201 x 402	4 3/4 x 7 15/16 x 15 13/16	16254078	Range Scandina Grey																			
B	C	120 x 201 x 469	4 3/4 x 7 15/16 x 18 1/2	16254311	Range Amber Beige																			
	Weight/unit (avg.)	21 kg	47 lb	16254312	Range Shaded Grey																			
C	Area/layer	0.87 m ²	9.35 ft ²	Sold in full cubes only																				
	Area/cube	3.48 m²	4 Rows	37.40 ft²																				
	Length/cube	28.94 lin. m	94.96 lin. ft	148 universal connectors included																				
	Weight/cube	1525 kg	3363 lb	Do not double stack in winter Production location St-Eustache																				

Laying Pattern



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Urbano Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm