



Virage Paver




| | Dimensions mm | Dimensions in. |
|--------------------|----------------------------|------------------------------------|
| | 80 x 300 x 300 | 3 1/8 x 11 7/8 x 11 7/8 |
| Weight/unit (avg.) | 16 kg | 36 lb |
| Unit/area (avg.) | 11.41 units/m ² | 1.06 units/ft ² |
| Area/layer | 1.05 m ² | 11.32 ft ² |
| Area/cube | 8.41 m² | 8 Rows 90.54 ft² |
| Length/row | 3.55 lin. m | 11.65 lin. ft |
| Length/cube | 28.42 lin. m | 93.23 lin. ft |
| Weight/cube | 1548 kg | 3413 lb |

| Code | Colour |
|-------------------------------|---------------------|
| | Prestige |
| 10303063 | Range Scandina Grey |
| Sold in full cubes | |
| Production location Cambridge | |


Typical Row




Laying Patterns




Beaded pattern




Circle pattern




Link pattern



Mosaic pattern



Random pattern



Wave pattern

TECHNICAL INFORMATION

| Product | Standard | Void Opening | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density | Absorption | Dimension Tolerance* |
|---------------------|------------|--------------|-------------------|----------------------|--|---------|------------|--|
| Virage Paver | CSA A231.2 | 47% | N/A | μ 50 MPa ≥ 45 MPa | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles | N/A | N/A | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).