



Eko Paver




Paver	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
A	70 x 180 x 360	2 3/4 x 7 x 14 1/8	10502891	Ash Grey Blend	
B	70 x 360 x 360	2 3/4 x 14 1/8 x 14 1/8	10502278	Granite Blend	
C	70 x 360 x 540	2 3/4 x 14 1/8 x 21 1/4	Sold in full cubes Production location Milton		
Weight/unit	19 kg	43 lb			
Area/layer	0.97 m ² 10 Rows	10.46 ft ²			
Area/cube	9.72 m²	104.6 ft²			
Length/row	3.24 lin. m	10.63 lin. ft			
Length/cube	32.4 lin. m	106.3 lin. ft			
Weight/cube	1551 kg	3421 lb			

Small Rectangle	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	70 x 180 x 360	2 3/4 x 7 x 14 1/8	127000525	Sierra Black	
Weight/unit	10 kg	23 lb	Sold in full cubes Production location Milton		
Area/layer	0.97 m ²	10.46 ft ²			
Area/cube	9.72 m²	104.6 ft²			
Length/row	5.4 lin. m 10 Rows	17.7 lin. ft			
Length/cube	54 lin. m	177.2 lin. ft			
Weight/cube	1534 kg	3384 lb			


Laying Patterns




Modular - Eko




Linear - Eko




Checkerboard -
Eko Small Rectangle




Running Bond -
Eko Small Rectangle



Offset 1/3 -
Eko Small Rectangle



Herringbone -
Eko Small Rectangle



Parquet -
Eko Small Rectangle

1 bag of sand covers approx. 155 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Eko Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.