


Vendome® 60 and 80 Paver




| 60 mm Not vehicular | | Dimensions mm | Dimensions in. |
|---------------------------|--------------------|----------------------------|------------------------------------|
| A | | 60 x 130 x 197 | 2 3/8 x 5 1/8 x 7 3/4 |
| B | | 60 x 130 x 262 | 2 3/8 x 5 1/8 x 10 5/16 |
| C | | 60 x 130 x 327 | 2 3/8 x 5 1/8 x 12 7/8 |
| | Weight/unit (avg.) | 4 kg | 9 lb |
| | Unit/area (avg.) | 30.50 units/m ² | 2.83 units/ft ² |
| | Area/layer | 1.05 m ² | 11.28 ft ² |
| | Area/cube | 8.40 m² | 8 Rows 90.24 ft² |
| | Length/row | 8.19 lin. m | 26.87 lin. ft |
| | Length/cube | 65.52 lin. m | 214.96 lin. ft |
| | Weight/cube | 1044 kg | 2302 lb |



| Code | Colour |
|----------|---------------------|
| | Prestige |
| 10554763 | Rockland Black |
| 10554761 | Range Margaux Beige |
| | Standard |
| 10554762 | Range Newport Grey |

Sold in full cubes only
Production location Bolton




| 80 mm | | Dimensions mm | Dimensions in. |
|-------|--------------------|----------------------------|------------------------------------|
| A | | 80 x 130 x 197 | 3 1/8 x 5 1/8 x 7 3/4 |
| B | | 80 x 130 x 262 | 3 1/8 x 5 1/8 x 10 5/16 |
| C | | 80 x 130 x 327 | 3 1/8 x 5 1/8 x 12 7/8 |
| | Weight/unit (avg.) | 5 kg | 12 lb |
| | Unit/area (avg.) | 30.50 units/m ² | 2.83 units/ft ² |
| | Area/layer | 1.05 m ² | 11.28 ft ² |
| | Area/cube | 8.40 m² | 8 Rows 90.24 ft² |
| | Qty/cube | A = 88 B = 96 C = 72 | |
| | Length/row | 7.86 lin. m | 25.80 lin. ft |
| | Length/cube | 62.90 lin. m | 206.40 lin. ft |
| | Weight/cube | 1382 kg | 3047 lb |




| Code | Colour |
|----------|---------------------|
| | Prestige |
| 10550002 | Rockland Black |
| 10559011 | Range Margaux Beige |
| | Standard |
| 10559010 | Range Newport Grey |


Sold in full cubes only
Production location Bolton



Laying Patterns



Linear



Modular

Techniseal® 1 bag of sand covers approx. : Vendome 60 - 44 ft² / Vendome 80 - 33 ft²

TECHNICAL INFORMATION

| Product | Standard | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density | Absorption | Dimension Tolerance* |
|---------------|------------|-------------------|----------------------|--|---------|------------|--|
| Vendome Paver | CSA A231.2 | N/A | μ 50 MPa ≥ 45 MPa | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles | N/A | N/A | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Runoff coefficient: 890 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).