





# Esbelto® DuraFusion Paver




|   | Dimensions mm              | Dimensions in.                     | Code                         | Colour            | Typical Row   |
|---|----------------------------|------------------------------------|------------------------------|-------------------|---|
|  | 80 x 305 x 610             | 3 1/8 x 12 x 24                    |                              | <b>DuraFusion</b> |   |
| Weight/unit   | 37 kg                      | 81 lb                              | 127001989                    | Oasis - <i>99</i> |  |
| Unit/area   | 5.382 units/m <sup>2</sup> | 0.50 unit/ft <sup>2</sup>          | 10551027                     | Marbella          |   |
| Area/layer  | 1.11 m <sup>2</sup>        | 12.00 ft <sup>2</sup>              | 10551024                     | Silverstone       |   |
| <b>Area/cube</b>  | <b>8.88 m<sup>2</sup></b>  | <b>8 Rows 96.00 ft<sup>2</sup></b> | 10550536                     | Hickory           |   |
| Length/layer  | 3.66 lin. m                | 12.00 lin. ft                      | Production location Metcalfe |                   |   |
| Length/cube   | 29.26 lin. m               | 96.00 lin. ft                      |                              |                   |   |
| Qty/cube  | 48 units                   | 48 units                           |                              |                   |   |
| Weight/cube   | 1764 kg                    | 3888 lb                            |                              |                   |   |


## Laying Patterns




Checkerboard




Running Bond



Offset 1/3



Herringbone

 1 bag of sand covers approx. 124 ft<sup>2</sup>

## TECHNICAL INFORMATION

| Product                         | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability  | Density | Absorption | Dimension Tolerance*   |
|---------------------------------|------------|-------------------|----------------------|--|---------|------------|--|
| <b>Esbelto DuraFusion Paver</b> | CSA A231.2 | N/A               | μ 50 MPa<br>≥ 45 MPa | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this Slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).