











Melville® 60 and Melville® 60 DuraFusion Slabs




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
  	A	60 x 190 x 380	2 3/8 x 7 1/2 x 15		
	B	60 x 380 x 380	2 3/8 x 15 x 15		
	C	60 x 380 x 570	2 3/8 x 15 x 22 7/16		
	Weight/unit (avg.)	19 kg	41 lb		
	Unit/area (avg.)	0.14 unit/m ²	1.46 units/ft ²		
	Area/layer	1.08 m ²	11.66 ft ²		
	Area/cube	10.80 m²	10 Rows	116.60 ft²	
	Qty/cube	80 units	80 units		
	Weight/cube	1500 kg	3307 lb		
			DuraFusion		
			127001987	Oasis - <i>99</i>	
			12051953	Marbella	
			12051954	Silverstone	
			12051955	Hickory	
			Prestige		
			12053046	Range Amber Beige	
			12052734	Range Margaux Beige	
			12052104	Range Chambord Grey	
			12052365	Range Scandina Grey	
			12052732	Rockland Black	
			Standard		
			12053045	Range Shaded Grey	
			12052733	Range Newport Grey	

Can be double stacked
 Production locations:
 DuraFusion - Metcalfe
 Prestige and Standard - Montreal, Quebec and Metcalfe


Laying Patterns



Modular



Linear

 1 bag of sand covers approx. 155 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.