



# Boulevard TLI 100 Paver



smooth [≡]	Colour
	White - Smooth
	Cinder Grey - Smooth
	Charcoal - Smooth
	Light Charcoal - Smooth
	Black ETX - Smooth
	Light Grey - Smooth
	Beige Grey - Smooth
	Beige - Smooth
	Red - Smooth


textured [≡≡≡]	Colour
	Cinder Grey - Granitech
	Light Charcoal - Granitech
	Charcoal - Granitech
	Light Grey - Granitech
	Beige Grey - Granitech
	Beige - Granitech
	Opal White - Granitech
	Stanstead Grey - Granitech
	Cambrian Brown - Granitech
	Cambrian Black - Granitech


150 x 300	Dimensions mm	Dimensions in.
	A	100 x 150 x 300 4 x 5 7/8 x 11 13/16
	Unit/area	22.22 units/m <sup>2</sup> 2.06 units/ft <sup>2</sup>
	Cube ft <sup>2</sup>	69.78 11.63 per row

Mass/ft <sup>2</sup>	22.33 kg	49.13 lb
Mass/ft <sup>2</sup>	23.63 kg	51.99 lb
Mass/ft <sup>2</sup>	28.83 kg	63.40 lb

Sold separately

Typical Row





300 x 300	Dimensions mm	Dimensions in.
	B	100 x 300 x 300 4 x 11 13/16 x 11 13/16
	Unit/area	11.11 units/m <sup>2</sup> 1.03 units/ft <sup>2</sup>
	Cube ft <sup>2</sup>	69.78 11.63 per row

Mass/ft <sup>2</sup>	22.33 kg	49.13 lb
Mass/ft <sup>2</sup>	23.63 kg	51.99 lb
Mass/ft <sup>2</sup>	28.83 kg	63.40 lb

Sold separately

Typical Row




300 x 700	Dimensions mm	Dimensions in.
	C	150 x 300 x 700 4 x 11 13/16 x 27 9/16
	Unit/area	22.8 units/m <sup>2</sup> 50.16 units/ft <sup>2</sup>
	Cube ft <sup>2</sup>	54.24 6.78 per row

Mass/ft <sup>2</sup>	22.8 kg	50.16 lb
----------------------	---------	----------


Smooth finish only

Typical Row




# Boulevard TLI 100 Paver - cont'd


## Laying Patterns



Linear



Linear



Modular  
50% A + 50% B

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Boulevard TLI 100 Paver</b>							
150 x 300	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm
300 x 300							Width: -1.0 to +2.0 mm
300 x 700							Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.