



# Boulevard TLI 150 Crescendo 125 Paver



smooth



| Colour                  |
|-------------------------|
| White - Smooth          |
| Cinder Grey - Smooth    |
| Charcoal - Smooth       |
| Light Charcoal - Smooth |
| Black ETX - Smooth      |
| Light Grey - Smooth     |
| Beige Grey - Smooth     |
| Beige - Smooth          |
| Red - Smooth            |


| textured                                                                          | Colour                     |
|-----------------------------------------------------------------------------------|----------------------------|
|  | Cinder Grey - Granitech    |
|                                                                                   | Light Charcoal - Granitech |
|                                                                                   | Charcoal - Granitech       |
|                                                                                   | Light Grey - Granitech     |
|                                                                                   | Beige Grey - Granitech     |
|                                                                                   | Beige - Granitech          |
|                                                                                   | Opal White - Granitech     |
|                                                                                   | Stanstead Grey - Granitech |
|                                                                                   | Cambrian Brown - Granitech |
|                                                                                   | Cambrian Black - Granitech |

|   |                      | Dimensions mm      | Dimensions in.             |
|---|----------------------|--------------------|----------------------------|
| A | A                    | 150 x 125 x 333.33 | 5 7/8 x 4 15/16 x 13 1/8   |
| B | B                    | 150 x 125 x 416.67 | 5 7/8 x 4 15/16 x 16 3/8   |
| C | C                    | 150 x 125 x 458.33 | 5 7/8 x 4 15/16 x 18       |
| D | D                    | 150 x 125 x 500    | 5 7/8 x 4 15/16 x 19 11/16 |
| E | E                    | 150 x 125 x 541.67 | 5 7/8 x 4 15/16 x 21 5/16  |
| F | F                    | 150 x 125 x 583.33 | 5 7/8 x 4 15/16 x 23       |
|   | Cube ft <sup>2</sup> | 53.80              | 10.76 per row              |
|   | Cube ft <sup>2</sup> | 53.80              | 10.76 per row              |
|   | Cube ft <sup>2</sup> | 43.04              | 10.76 per row              |


|                      |         |         |
|----------------------|---------|---------|
| Mass/ft <sup>2</sup> | 32.6 kg | 71.7 lb |
| Mass/ft <sup>2</sup> | 34.4 kg | 75.7 lb |
| Mass/ft <sup>2</sup> | 43.6 kg | 95.9 lb |

Units are not sold separately

## Typical Row



## Laying Pattern



Linear

## TECHNICAL INFORMATION

| Product                                                | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability                                        | Density | Absorption | Dimension Tolerance*                                                 |
|--------------------------------------------------------|------------|-------------------|----------------------|------------------------------------------------------------------------------|---------|------------|----------------------------------------------------------------------|
| <b>Boulevard TLI 150</b><br><b>Crescendo 125 Paver</b> |            |                   |                      |                                                                              |         |            |                                                                      |
| 125 x 333.33                                           |            |                   |                      |                                                                              |         |            |                                                                      |
| 125 x 416.67                                           |            |                   |                      |                                                                              |         |            |                                                                      |
| 125 x 458.33                                           | CSA A231.2 | N/A               | μ 50 MPa<br>≥ 45 MPa | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |
| 125 x 500                                              |            |                   |                      |                                                                              |         |            |                                                                      |
| 125 x 541.67                                           |            |                   |                      |                                                                              |         |            |                                                                      |
| 125 x 583.33                                           |            |                   |                      |                                                                              |         |            |                                                                      |

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.