


Grande Smooth Wall




375 Standard



	Dimensions mm	Dimensions in.
	200 x 375 x 1000	7 7/8 x 14 3/4 x 39 3/8
Weight/unit	161 kg	360 lb
Area/layer	5.00 units/m ²	0.46 unit/ft ²
Area/cube	1.80 m ²	19.56 ft ²
Length/cube	9.00 lin. m	29.60 lin. ft
Qty/cube	9 units	9 units
Weight/cube	1500 kg	3300 lb

Code	Colour
129000448	Grey
Sold in full cubes	
Can be double stacked	
Production location Metcalfe	

Typical Row




750 Standard



	Dimensions mm	Dimensions in.
	200 x 750 x 1000	7 7/8 x 29 1/2 x 39 3/8
Weight/unit	328 kg	726 lb
Area/layer	5.00 units/m ²	0.46 unit/ft ²
Area/cube	0.80 m ²	8.70 ft ²
Length/cube	4.00 lin. m	13.10 lin. ft
Qty/cube	4 units	4 units
Weight/cube	1350 kg	2970 lb

Code	Colour
129000449	Grey
Sold in full cubes	
Can be double stacked	
Production location Metcalfe	

Typical Row




1125 Standard



	Dimensions mm	Dimensions in.
	200 x 1125 x 1000	7 7/8 x 44 5/16 x 39 3/8
Weight/unit	483 kg	1065 lb
Area/layer	5.00 units/m ²	0.46 unit/ft ²
Area/cube	0.60 m ²	6.45 ft ²
Length/cube	3.00 lin. m	9.90 lin. ft
Qty/cube	3 units	3 units
Weight/cube	1450 kg	3190 lb

Code	Colour
129000452	Grey
Sold in full cubes	
Can be double stacked	
Production location Metcalfe	

Typical Row





TECHNICAL INFORMATION



Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Smooth Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm



The information contained in these technical documents is supplied for information purposes only. Any application of the information is the sole responsibility of the installer. The installer must ensure that the installation and use of retaining wall projects comply with local regulations and code requirements. A qualified engineer must be consulted for final design for construction purposes. Oldcastle Building Products Canada, Inc. and its affiliates cannot be held responsible for the improper use of information contained in these technical documents.

Grande Smooth Wall

Corner Unit	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	200 x 500 x 1000	7 7/8 x 19 11/16 x 39 3/8	129000451	Grey	
Weight/unit	213 kg	469 lb	Can be double stacked		
Unit/area	3.33 units/m ²	0.31 unit/ft ²	Production location Metcalfe		
Qty/cube	6 units*	6 units*			
Weight/cube	1278 kg	2811 lb			

* 6 units equal: 3 right units, 3 left units

Step 175	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	175 x 438 x 1000	6 7/8 x 17 1/4 x 39 3/8	16202415	Grey	
Weight/unit	175 kg	386 lb	Sold in full cubes		
Length/cube	1.20 lin. m	19.68 lin. ft	Can be double stacked		
Qty/cube	6 units	6 units	Production location Cambridge		
Weight/cube	1070 kg	2358 lb			

Capping 438	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	200 x 438 x 1000	7 7/8 x 17 1/4 x 39 3/8	129000451	Grey	
Weight/unit	194 kg	427 lb	Sold in full cubes		
Unit/area	5.00 units/m ²	0.46 unit/ft ²	Can be double stacked		
Qty/cube	6 units	6 units	Production location Metcalfe		
Weight/cube	1162 kg	2561 lb			

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Smooth Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

The information contained in these technical documents is supplied for information purposes only. Any application of the information is the sole responsibility of the installer. The installer must ensure that the installation and use of retaining wall projects comply with local regulations and code requirements. A qualified engineer must be consulted for final design for construction purposes. Oldcastle Building Products Canada, Inc. and its affiliates cannot be held responsible for the improper use of information contained in these technical documents.