




Kensington Paver




Rectangle	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
		80 x 209 x 279	3 1/8 x 8 1/4 x 11	10500847	Sierra Black
	Weight/unit	10 kg	23 lb	Sold in full cubes only Production location Milton	
	Units/area	-	1.55 units/ft²		
	Area/section	-	23.17 ft²		
	Area/cube	-	92.70 ft²		
	Length/section	-	25 lin. ft		
	Length/cube	-	100 lin. ft		
	Qty	144 units/cube	36 units/section		
	Weight	1498 kg	3304 lb		

Mixed Bundle		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
 C	C	80 x 279 x 419	3 1/8 x 11 x 16 1/2	10503384	Ash Grey Blend	
	Weight/unit	21.36 kg	47.10 lb	10500842	Canyon Grey Blend	
	Units/area	-	0.78 unit/ft²	10500843	Desert Grey Blend	
	Qty/cube	36 units	36 units	10506472	Granite Blend	
	B	80 x 279 x 279	3 1/8 x 11 x 11	Sold in full cubes only Production location Milton		
Weight/unit	14.33 kg	31.60 lb				
Units/area	-	1.17 units/ft²				
 B	Qty/cube	36 units	36 units			
	A	80 x 139 x 279	3 1/8 x 5 1/2 x 11			
	Weight/unit	7.07 kg	15.60 lb			
 A	Units/area	-	2.32 units/ft²			
	Qty/cube	36 units	36 units			
	Area/cube	-	92.43 ft²			
	Weight/cube	1515 kg	3341 lb			

Laying Pattern




Pattern 1:
3 Stone Random



Pattern 2:
3 Stone Running Bond



Pattern 3: Herringbone
100% Rectangle



Pattern 4: Running Bond
100% Rectangle

 1 bag of sand covers approx. 37 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Kensington Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient (mixed bundle): 247 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.