

Keystone Wall and Capping




Compact Straight-Face Wall Unit



	Dimensions mm	Dimensions in.
	204 x 305 x 457	8 x 12 x 18
Weight/unit	45 kg	99 lb
Unit/area	10.80 units/m²	1.00 unit/ft²
Area/cube	3.70 m²	40.00 ft²
Qty/cube	40 units	5 Rows
Weight/cube	1832 kg	4039 lb

Code	Colour
16055000	Smoke Grey

Typical Row




Corner Wall Unit




	Dimensions mm	Dimensions in.
	204 x 230 x 450	8 x 9 x 18
Weight/unit	52 kg	114 lb
Unit/area	7.20 units/m²	0.67 unit/ft²
Area/cube	2.79 m²	30.00 ft²
Qty/cube	20 units	2 Rows
Weight/cube	1044 kg	2296 lb

Code	Colour
16052390	Smoke Grey

Typical Row



Laying Pattern



Linear


Straight-Face Capping



	Dimensions mm	Dimensions in.
	102 x 267 x 432	4 x 10 1/2 x 17
Weight/unit	30 kg	64 lb
Unit/length	2.20 units/lin. m	0.67 unit/lin. ft
Area/cube	2.60 m ²	28.00 ft ²
Qty/cube	56 units	7 Rows
Weight/cube	1655 kg	3640 lb

Code	Colour
16054730	Smoke Grey

Typical Row



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Keystone Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm
Keystone Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Application: Supporting walls. For additional details see our landscaping installation guide on our website.

The information contained in these technical documents is supplied for information purposes only. Any application of the information is the sole responsibility of the installer. The installer must ensure that the installation and use of retaining wall projects comply with local regulations and code requirements. A qualified engineer must be consulted for final design for construction purposes. Oldcastle Building Products Canada, Inc. and its affiliates cannot be held responsible for the improper use of information contained in these technical documents.