




Mega Melville® Paver




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row		
	80 x 570 x 950	3 1/8 x 22 7/16 x 37 3/8		Prestige			
	Weight/unit	101 kg	222 lb	10550530		Range Amber Beige (1)	
	Unit/area	1.85 units/m²	0.17 unit/ft²	10551112		Range Margaux Beige (2)	
	Area/layer	1.08 m²	11.66 ft²	10550464		Range Chambord Grey (2)	
	Area/cube	7.56 m²	7 Rows	81.62 ft²		10559045	Range Scandina Grey (1)
	Length/layer	1.90 lin. m	6.23 lin. ft	10550531		Rockland Black (2)	
	Length/cube	13.29 lin. m	43.60 lin. ft			Standard	
	Qty/cube	14 units	14 units	10550529		Range Shaded Grey (2)	
	Weight/cube	1410 kg	3109 lb	10550534		Range Newport Grey (2)	
Sold in full cubes only							
Production locations:							
Metcalfe (1)							
Milton (2)							


Laying Patterns



Linear



Herringbone



Modular
83% Melville 80
17% Mega Melville 80

 1 bag of sand covers approx. 217 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mega Melville Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this Slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).