


Mondrian® Plus 60 Small Rectangle Paver




	Dimensions mm	Dimensions in.
	60 x 330 x 165	2 3/8 x 13 x 6 1/2
Weight/unit	7 kg	16 lb
Unit/area	18.52 units/m ²	1.71 units/ft ²
Area/layer	0.82 m ²	8.79 ft ²
Area/cube	9.84 m²	12 Rows
Length/row	4.95 lin. m	16.25 lin. ft
Length/cube	59.43 lin. m	195.00 lin. ft
Qty/cube	180 units	180 units
Weight/cube	1283 kg	2830 lb

Code	Colour	Typical Row
	Prestige	
12052557	Rockland Black	
Sold in full cubes only		
Production location Bolton		

Laying Patterns



Linear



Herringbone

Techniseal 1 bag of sand covers approx. 38 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 60 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.
The Mondrian Plus 60 Slab is compatible with the Mondrian Plus 60 small rectangle paver for non-vehicular application only.