

Urbano® Wall




smooth



		Dimensions mm	Dimensions in.	Code	Colour	Typical Row																					
	A	120 x 201 x 335	4 3/4 x 7 15/16 x 13 3/16	16254078	Range Scandina Grey	<table><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td>B</td><td>A</td><td>C</td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr></table>							B	A	C												
B	A	C																									
	B	120 x 201 x 402	4 3/4 x 7 15/16 x 15 13/16	16254311	Range Amber Beige																						
	C	120 x 201 x 469	4 3/4 x 7 15/16 x 18 1/2	16254312	Range Shaded Grey																						
	Weight/unit (avg.)	21 kg	47 lb	Sold in full cubes only 148 universal connectors included Do not double stack in winter Production location St-Eustache																							
	Area/layer	0.87 m ²	9.35 ft ²																								
	Area/cube	3.48 m ²	4 Rows 37.40 ft ²																								
	Length/cube	28.94 lin. m	94.96 lin. ft																								
	Weight/cube	1525 kg	3363 lb																								

Laying Pattern



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Urbano Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm