




Wilfrid Slab




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
A		A	60 x 570 x 380		Prestige	
		B	60 x 570 x 570	12051189	Range Amber Beige	
B		C	60 x 570 x 950	12051213	Range Scandina Grey	
		Weight/unit (avg.)	53 kg		Standard	
C		Area/layer (avg.)	1.05 m ²	127000957	Range Newport Grey	
		Area/cube	9.72 m²			
			9 Rows			
		Area/cube	104.94 ft²			
		Weight/cube	1422 kg		Sold in full cubes	
			3150 lb		Production location Milton	

Laying Patterns



Modular



Linear

 1 bag of sand covers approx. 244 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wilfrid Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.