




Zen Paver




| | Dimensions mm | Dimensions in. |
|---|----------------------------|---------------------------|
|  | 80 x 190 x 380 | 3 1/8 x 7 1/2 x 15 |
| Weight/unit (avg.) | 12 kg | 26 lb |
| Unit/area (avg.) | 18.04 units/m ² | 3.1 units/ft ² |
| Area/layer | 0.87 m ² | 9.33 ft ² |
| Area/cube | 7.83 m² | 9 Rows |
| Qty/cube | 108 units | 108 units |
| Length/row | 4.52 lin. m | 14.84 lin. ft |
| Length/cube | 40.72 lin. m | 133.58 lin. ft |
| Weight/cube | 1286 kg | 2837 lb |


| Code | Colour |
|----------------------------|----------------------|
| | Prestige |
| 10300745 | Range Amber Beige |
| 10301003 | Range Scandinia Grey |
| Sold in full cubes | |
| Production location Bolton | |



Laying Patterns



Linear



Linear

TECHNICAL INFORMATION

| Product | Standard | Void Opening | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density | Absorption | Dimension Tolerance* |
|-----------|------------|--------------|-------------------|----------------------|--|---------|------------|--|
| Zen Paver | CSA A231.2 | 27% | N/A | μ 50 MPa ≥ 45 MPa | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles | N/A | N/A | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
 Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).