




Esbelto® and Esbelto® DuraFusion Slabs




	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	60 x 305 x 610	2 3/8 x 12 x 24		DuraFusion	
Weight/unit	26 kg	57 lb	127001990	Oasis - <i>91</i>	
Area/unit	0.186 m²	2.00 ft²	12052376	Marbella	
Area/layer	1.11 m²	12.00 ft²	12052375	Silverstone	
Area/cube	11.10 m²	10 Rows	12052896	Hickory	
Qty/cube	60 units	60 units		Prestige	
Weight/cube	1546 kg	3409 lb	12051114	Range Amber Beige	
			12051112	Range Scandina Grey	
			Production locations:		
			DuraFusion - Metcalfe		
			Prestige - Montreal		


Laying Patterns




Checkerboard



Running Bond



Offset 1/3



Herringbone

 **Techniseal** 1 bag of sand covers approx. 165 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Esbelto Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.