


Grande Smooth Wall




Walls

375 Standard		Dimensions mm	Dimensions in.
		200 x 375 x 1000	7 7/8 x 14 3/4 x 39 3/8
	Weight/unit	161 kg	360 lb
	Area/layer	5.00 units/m ²	0.46 unit/ft ²
	Area/cube	1.80 m ²	19.56 ft ²
	Length/cube	9.00 lin. m	29.60 lin. ft
	Qty/cube	9 units	9 units
	Weight/cube	1500 kg	3300 lb



Code	Colour
129000448	Grey
Can be double stacked	
Production location Quebec and Metcalfe	

Typical Row




750 Standard		Dimensions mm	Dimensions in.
		200 x 750 x 1000	7 7/8 x 29 1/2 x 39 3/8
	Weight/unit	328 kg	726 lb
	Area/layer	5.00 units/m ²	0.46 unit/ft ²
	Area/cube	0.80 m ²	8.70 ft ²
	Length/cube	4.00 lin. m	13.10 lin. ft
	Qty/cube	4 units	4 units
	Weight/cube	1350 kg	2970 lb



Code	Colour
129000449	Grey
Can be double stacked	
Production location Quebec and Metcalfe	

Typical Row




1125 Standard		Dimensions mm	Dimensions in.
		200 x 1125 x 1000	7 7/8 x 44 5/16 x 39 3/8
	Weight/unit	483 kg	1065 lb
	Area/layer	5.00 units/m ²	0.46 unit/ft ²
	Area/cube	0.60 m ²	6.45 ft ²
	Length/cube	3.00 lin. m	9.90 lin. ft
	Qty/cube	3 units	3 units
	Weight/cube	1450 kg	3190 lb



Code	Colour
129000452	Grey
Can be double stacked	
Production location Quebec and Metcalfe	

Typical Row



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Smooth Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

The information contained in these technical documents is supplied for information purposes only. Any application of the information is the sole responsibility of the installer. The installer must ensure that the installation and use of retaining wall projects comply with local regulations and code requirements. A qualified engineer must be consulted for final design for construction purposes. Oldcastle Building Products Canada, Inc. and its affiliates cannot be held responsible for the improper use of information contained in these technical documents.

Grande Smooth Wall

Corner Unit




	Dimensions mm	Dimensions in.
	200 x 500 x 1000	7 7/8 x 19 11/16 x 39 3/8
Weight/unit	213 kg	469 lb
Unit/area	3.33 units/m ²	0.31 unit/ft ²
Qty/cube	6 units*	6 units*
Weight/cube	1278 kg	2811 lb

* 6 units equal: 3 right units, 3 left units

Code	Colour
129000451	Grey
Call for custom colour information	
Can be double stacked	
Production location Quebec and Metcalfe	

Typical Row




Step 175



	Dimensions mm	Dimensions in.
	175 x 438 x 1000	6 7/8 x 17 1/4 x 39 3/8
Weight/unit	175 kg	386 lb
Length/cube	1.20 lin. m	19.68 lin. ft
Qty/cube	6 units	6 units
Weight/cube	1070 kg	2358 lb

Code	Colour
16202415	Grey
Can be double stacked	
Production location Cambridge	

Typical Row




Capping 438



	Dimensions mm	Dimensions in.
	200 x 438 x 1000	7 7/8 x 17 1/4 x 39 3/8
Weight/unit	194 kg	427 lb
Unit/area	5.00 units/m ²	0.46 unit/ft ²
Qty/cube	6 units	6 units
Weight/cube	1162 kg	2561 lb

Code	Colour
129000450	Grey
Can be double stacked	
Production location Quebec and Metcalfe	

Typical Row



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Grande Smooth Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

The information contained in these technical documents is supplied for information purposes only. Any application of the information is the sole responsibility of the installer. The installer must ensure that the installation and use of retaining wall projects comply with local regulations and code requirements. A qualified engineer must be consulted for final design for construction purposes. Oldcastle Building Products Canada, Inc. and its affiliates cannot be held responsible for the improper use of information contained in these technical documents.