

New Melia 6 x 6 DuraFusion Paver




textured







	Dimensions mm	Dimensions in.
	60 x 152 x 152	2 3/8 x 6 x 6
Weight/unit	3 kg	7 lb
Area/unit	0.02 m²	0.25 ft²
Area/layer	1.11 m²	12.0 ft²
Area/cube	11.15 m²	10 Rows
Qty/cube	480 units	480 units
Weight/cube	1521 kg	3354 lb

Code	Colour	Typical Row
	DuraFusion	
127002107	Oasis	
127002105	Marbella	
127002106	Hickory	
Production location Metcalfe		
		

Laying Patterns



Checkerboard



Running Bond

Techniseal 1 bag of sand covers approx. 95 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melia 6 x 6 DuraFusion Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.