



Melville® 60 and Melville® 60 DuraFusion Slabs




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
A B C	A	60 x 190 x 380	2 3/8 x 7 1/2 x 15		DuraFusion	
	B	60 x 380 x 380	2 3/8 x 15 x 15	127001987	Oasis - <i>91</i>	
	C	60 x 380 x 570	2 3/8 x 15 x 22 7/16	12051953	Marbella	
	Weight/unit (avg.)	19 kg	41 lb	12051954	Silverstone	
	Unit/area (avg.)	0.14 unit/m²	1.46 units/ft²	12051955	Hickory	
	Area/layer	1.08 m²	11.66 ft²		Prestige	
	Area/cube	10.80 m²	10 Rows	12053046	Range Amber Beige	
	Qty/cube	80 units	80 units	12052734	Range Margaux Beige	
	Weight/cube	1500 kg	3307 lb	12052104	Range Chambord Grey	
				12052365	Range Scandina Grey	
				12052732	Rockland Black	
					Standard	
				12053045	Range Shaded Grey	
				12052733	Range Newport Grey	

Can be double stacked
Production locations:
DuraFusion - Metcalfe
Prestige and Standard - Montreal, Quebec and Metcalfe

Laying Patterns



Modular



Linear

1 bag of sand covers approx. 155 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.