



Melville® 80 and Melville® 80 DuraFusion Pavers




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
A B C	A	80 x 190 x 380	3 1/8 x 7 1/2 x 15		DuraFusion	
	B	80 x 380 x 380	3 1/8 x 15 x 15	127001988	Oasis - <i>91</i>	
	C	80 x 380 x 570	3 1/8 x 15 x 22 7/16	10554893	Marbella	
	Weight/unit (avg.)	25 kg	55 lb	10555066	Silverstone	
	Unit/area (avg.)	7.39 units/m ²	0.69 unit/ft ²	10555067	Hickory	
	Area/layer	1.08 m ²	11.66 ft ²		Prestige	
	Area/cube	8.64 m²	8 Rows	10550869	Range Amber Beige	
	Length/row	3.04 lin. m	9.97 lin. ft	10550447	Range Margaux Beige	
	Length/cube	24.32 lin. m	79.79 lin. ft	10554764	Range Chambord Grey	
	Weight/cube	1598 kg	3523 lb	10550446	Range Scandina Grey	
				10550557	Rockland Black	
					Standard	
				10550868	Range Shaded Grey	
				10550558	Range Newport Grey	

Production locations:
DuraFusion - Metcalfe
Prestige and Standard - Montreal, Quebec and Metcalfe

Laying Patterns



Linear



Modular

Techniseal 1 bag of sand covers approx. 116 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 and DuraFusion Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.