



Mondrian® Plus 60 Slab




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
A		A	60 x 165 x 330	2 3/8 x 6 1/2 x 13	Prestige 12052893 Range Margaux Beige 12052894 Range Amboise Beige 12052566 Range Scandina Grey	
		B	60 x 330 x 330	2 3/8 x 13 x 13		
		C	60 x 330 x 495	2 3/8 x 13 x 19 1/2		
B		Weight/unit (avg.)	13 kg	28 lb	Standard 12052891 Range Norvick Grey 12052892 Range Newport Grey Can be double stacked Production location Montreal, Quebec and Metcalfe	
		Area/unit	0.11 m²	1.17 ft²		
		Area/layer	0.98 m²	10.55 ft²		
C		Area/cube	11.76 m²	12 Rows	126.60 ft²	
		Qty/cube	A = 48	B = 48	C = 24	
		Weight/cube	1551 kg	3419 lb		


Laying Patterns



Linear
100% Mix A, B, C



Modular
100% Mix A, B, C



Modular
100% Mix A, B, C

Techniseal 1 bag of sand covers approx. 57 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.