

# Mondrian® Plus 80 Small Rectangle Paver




Pavers




	Dimensions mm	Dimensions in.
	80 x 165 x 330	3 1/8 x 6 1/2 x 13
Weight/unit	10 kg	21 lb
Unit/area	18.52 units/m <sup>2</sup>	1.71 units/ft <sup>2</sup>
Area/layer	0.82 m <sup>2</sup>	8.79 ft <sup>2</sup>
<b>Area/cube</b>	<b>7.38 m<sup>2</sup></b>	<b>9 Rows 79.11 ft<sup>2</sup></b>
Length/row	4.95 lin. m	16.25 lin. ft
Length/cube	59.43 lin. m	195.00 lin. ft
Qty/cube	135 units	135 units
Weight/cube	1302 kg	2871 lb


Code	Colour
	<b>Prestige</b>
10550516	Rockland Black
Can be double stacked	
Production location Metcalfe	



## Laying Patterns



Linear



Herringbone

1 bag of sand covers approx. 29 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Mondrian Plus 80 Small Rectangle Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).