



Wilfrid Slab




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row	
A		A	60 x 570 x 380	2 3/8 x 22 7/16 x 15			
		B	60 x 570 x 570	2 3/8 x 22 7/16 x 22 7/16			
B		C	60 x 570 x 950	2 3/8 x 22 7/16 x 37 3/8			
		Weight/unit (avg.)	53 kg	117 lb			
C		Area/layer (avg.)	1.05 m²	11.66 ft²			
		Area/cube	9.72 m²	9 Rows			104.94 ft²
		Weight/cube	1422 kg	3150 lb			

Laying Patterns



Modular



Linear

Techniseal 1 bag of sand covers approx. 244 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wilfrid Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.