




Brooklyn Paver




| | Dimensions mm | Dimensions in. | Code | Colour | Typical Row |
|---|---------------------------|-----------------------|------------------------------|------------------|-------------|
|  | 60 x 230 x 76 | 2 3/8 x 9 x 3 | | TrueColor | |
| Weight/unit | 2.3 kg | 5.1 lb | 10151722 | Midnight | |
| Unit/area | 0.02 m ² | 0.188 ft ² | 10150880 | Rosewood | |
| Area/layer | 0.96 m ² | 10.3 ft ² | Sold in full cubes | | |
| Area/cube | 9.58 m² | 10 Rows | 103.13 ft² | | |
| Qty/cube | 550 units | 550 units | Production location Milton | | |
| Weight/cube | 1272 kg | 2805 lb | | | |

| | | | | |
|--|--|--|--|--|
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |


Laying Pattern




Checkerboard




Running Bond



Offset 1/3



Herringbone

 1 bag of sand covers approx. 70 ft²

TECHNICAL INFORMATION

| Product | Standard | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density | Absorption | Dimension Tolerance* |
|-----------------------|------------|-------------------|----------------------|--|---------|------------|--|
| Brooklyn Paver | CSA A231.2 | N/A | μ 50 MPa ≥ 45 MPa | 225 g/m ² after 28 cycles 500 g/m ² after 49 cycles | N/A | N/A | Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm |

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.