

# Institutional Curbs



## High Rised Curb A1 1 2M

|                 | Dimensions mm    | Dimensions in. |
|-----------------|------------------|----------------|
|                 | 300 x 150 x 1200 | 12 x 6 x 48    |
| Weight/unit     | 101 kg           | 222 lb         |
| Length/cube     | 16.8 lin. m      | 55.1 lin. ft   |
| <b>Qty/cube</b> | <b>14 units</b>  | <b>2 Rows</b>  |
| Weight/cube     | 1450 kg          | 3197 lb        |

|               |
|---------------|
| <b>Code</b>   |
| 14209025      |
| <b>Colour</b> |
| Grey          |



## Transition Curb 175 to 300 AB1 (L) - BA1 (R)

|                 | Dimensions mm          | Dimensions in.   |                 |
|-----------------|------------------------|------------------|-----------------|
|                 | 175 to 300 x 150 x 500 | 7 to 12 x 6 x 20 |                 |
| Weight/unit     | 36 kg                  | 79 lb            |                 |
| Length/cube     | 8 lin. m               | 26.3 lin. ft     |                 |
| <b>Qty/cube</b> | <b>16 units</b>        | <b>2 Rows</b>    | <b>16 units</b> |
| Weight/cube     | 640 kg                 | 1411 lb          |                 |

|               |
|---------------|
| <b>Code</b>   |
| 14209034 (L)  |
| 14209035 (R)  |
| <b>Colour</b> |
| Grey          |
| Sold in pairs |



## Low Rised Curb B1 1 2M

|                 | Dimensions mm    | Dimensions in. |
|-----------------|------------------|----------------|
|                 | 200 x 150 x 1200 | 8 x 6 x 48     |
| Weight/unit     | 71 kg            | 156 lb         |
| Length/cube     | 25.2 lin. m      | 82.7 lin. ft   |
| <b>Qty/cube</b> | <b>21 units</b>  | <b>3 Rows</b>  |
| Weight/cube     | 1520 kg          | 3350 lb        |

|               |
|---------------|
| <b>Code</b>   |
| 14209036      |
| <b>Colour</b> |
| Grey          |



## Inside Corner

|                 | Dimensions mm   | Dimensions in. |                 |
|-----------------|-----------------|----------------|-----------------|
|                 | 300 x 150 x 300 | 12 x 6 x 12    |                 |
| Weight/unit     | 47 kg           | 104 lb         |                 |
| Length/cube     | 7.2 lin. m      | 23.6 lin. ft   |                 |
| <b>Qty/cube</b> | <b>24 units</b> | <b>2 Rows</b>  | <b>24 units</b> |
| Weight/cube     | 1190 kg         | 2623 lb        |                 |

|               |
|---------------|
| <b>Code</b>   |
| 14209039      |
| <b>Colour</b> |
| Grey          |



## Transition Curb 200 to 300 AB1 (L) - BA1 (R)

|                 | Dimensions mm           | Dimensions in.   |
|-----------------|-------------------------|------------------|
|                 | 200 to 300 x 150 x 1200 | 8 to 12 x 6 x 48 |
| Weight/unit     | 94 kg                   | 207 lb           |
| Length/cube     | 9.6 lin. m              | 31.5 lin. ft     |
| <b>Qty/cube</b> | <b>8 units</b>          | <b>2 Rows</b>    |
| Weight/cube     | 810 kg                  | 1786 lb          |

|               |
|---------------|
| <b>Code</b>   |
| 14209032 (L)  |
| 14209033 (R)  |
| <b>Colour</b> |
| Grey          |



## Outside Corner

|                 | Dimensions mm   | Dimensions in. |                 |
|-----------------|-----------------|----------------|-----------------|
|                 | 300 x 150 x 300 | 12 x 6 x 12    |                 |
| Weight/unit     | 47 kg           | 104 lb         |                 |
| Length/cube     | 7.2 lin. m      | 23.6 lin. ft   |                 |
| <b>Qty/cube</b> | <b>24 units</b> | <b>2 Rows</b>  | <b>24 units</b> |
| Weight/cube     | 1190 kg         | 2623 lb        |                 |

|               |
|---------------|
| <b>Code</b>   |
| 14209041      |
| <b>Colour</b> |
| Grey          |

## Quantity of curved edges required for rotation angle of standardized curves

| Angle Curve | 45° | 90° | 135° | 180° | 225° | 270° | 315° | 360° |
|-------------|-----|-----|------|------|------|------|------|------|
| 0.625       | -   | 1   | -    | 2    | -    | 3    | -    | 4    |
| 1.25        | 1   | 2   | 3    | 4    | 5    | 6    | 7    | 8    |
| 2.50        | 2   | 4   | 6    | 8    | 10   | 12   | 14   | 16   |
| 5.00        | 4   | 8   | 12   | 16   | 20   | 24   | 28   | 32   |
| 7.5         | 6   | 12  | 18   | 24   | 30   | 36   | 42   | 48   |
| 10.00       | 8   | 16  | 24   | 32   | 40   | 48   | 56   | 64   |



## Outside Curved C1 Exposed

|                 | Dimensions mm    | Dimensions in. |                 |
|-----------------|------------------|----------------|-----------------|
|                 | 300 x 150 x 1000 | 12 x 6 x 40    |                 |
| Weight/unit     | 100 kg           | 220 lb         |                 |
| Length/cube     | 12 lin. m        | 39.4 lin. ft   |                 |
| <b>Qty/cube</b> | <b>12 units</b>  | <b>2 Rows</b>  | <b>12 units</b> |
| Weight/cube     | 1260 kg          | 2778 lb        |                 |

|                 |
|-----------------|
| <b>Code</b>     |
| 14209026* 0.625 |
| 14209027 1.25   |
| 14209028 2.50   |
| 14209029 5.00   |
| 14209030 7.50   |
| 14209031 10.00  |

\* The Outside Curved C1 Exposed curb, code 14209026, comes in 10 pieces per pallet.

|               |
|---------------|
| <b>Colour</b> |
| Grey          |

## TECHNICAL INFORMATION

| Product                                                                                                                                | Standard    | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability | Density                | Absorption | Dimension Tolerance*                                 |
|----------------------------------------------------------------------------------------------------------------------------------------|-------------|-------------------|----------------------|---------------------------------------|------------------------|------------|------------------------------------------------------|
| <b>Institutional Curbs</b><br>High Rised Curb<br>Low Rised Curb<br>Transition Curb<br>Inside Corner<br>Outside Corner<br>Outside Curve | BNQ2624-210 | ≥ 4.5 MPa         | 45 MPa               | 500 g/m <sup>2</sup>                  | 2300 kg/m <sup>3</sup> | 5 %        | Length: ±5.0 mm<br>Width: ±3.0 mm<br>Height: ±5.0 mm |

For additional details see our landscaping installation guide on our website.