




Kensington Smooth Paver




Rectangle	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	80 x 209 x 279	3 1/8 x 8 1/4 x 11	10506699	Sierra Black	
	Weight/unit	10 kg	Sold in full cubes only		
	Units/area	-	Production location Milton		
	Area/section	-			
	Area/cube	-			
	Length/section	-			
	Length/cube	-			
	Qty	144 units/cube			
	Weight	1498 kg			




Mixed Bundle	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	C	80 x 279 x 419	10506622	Ash Grey Blend	
	Weight/unit	21.36 kg	10506693	Canyon Grey Blend	
	Units/area	-	10506694	Desert Grey Blend	
	Qty/cube	36 units	10506692	Granite Blend	
	B	80 x 279 x 279	Sold in full cubes only		
	Weight/unit	14.33 kg	Production location Milton		
	Units/area	-			
	Qty/cube	36 units			
	A	80 x 139 x 279			
	Weight/unit	7.07 kg			
	Units/area	-			
	Qty/cube	36 units			
	Area/cube	-			
	Weight/cube	1531 kg			




Laying Pattern




Pattern 1:
3 Stone Random



Pattern 2:
3 Stone Running Bond



Pattern 3: Herringbone
100% Rectangle



Pattern 4: Running Bond
100% Rectangle

 1 bag of sand covers approx. 37 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Kensington Smooth Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient (mixed bundle): 247 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.