

Leno Capping



smooth




textured



Bullnose	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	40 kg	88 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
Qty/cube	24 units	2 Rows
Weight/cube	969 kg	2136 lb

Code	Colour
121000280	Range Amber Beige
121000278	Range Shaded Grey
121000277	Range Scandina Grey
121000279	Rockland Black
Cannot be double stacked	
Production location St-Eustache	


Typical Row



Straight	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
Qty/cube	24 units	2 Rows
Weight/cube	925 kg	2038 lb

Code	Colour
121000286	Range Amber Beige
121000285	Range Scandina Grey
121000284	Rockland Black
Cannot be double stacked	
Production location St-Eustache	


Typical Row



Lafitt	Dimensions mm	Dimensions in.
	60 x 305 x 915	2 3/8 x 12 x 36
Weight/unit	39 kg	85 lb
Unit/area	3.58 units/lin. m	0.33 unit/lin. ft
Length/row	10.98 lin. m	36 lin. ft
Length/cube	21.96 lin. m	72 lin. ft
Qty/cube	24 units	2 Rows
Weight/cube	925 kg	2038 lb

Code	Colour
121000283	Range Margaux Beige
121000282	Range Newport Grey
121000281	Rockland Black
Cannot be double stacked	
Production location St-Eustache	

Typical Row



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Leno Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ³	10.4%	Length: ±3.2 mm Width : ±3.2 mm Height: ±3.2 mm