


Melville® 60 and Melville® 60 DuraFusion Slabs



A

B

C

	Dimensions mm	Dimensions in.	
A	60 x 190 x 380	2 3/8 x 7 1/2 x 15	
B	60 x 380 x 380	2 3/8 x 15 x 15	
C	60 x 380 x 570	2 3/8 x 15 x 22 7/16	
Weight/unit (avg.)	19 kg	41 lb	
Unit/area (avg.)	0.14 unit/m²	1.46 units/ft²	
Area/layer	1.08 m²	11.66 ft²	
Area/cube	10.80 m²	10 Rows	116.60 ft²
Qty/cube	80 units	80 units	
Weight/cube	1500 kg	3307 lb	

Code	Colour
DuraFusion	
127001987	Oasis - <i>M</i> (1) 
12051953	Marbella (1) 
12051954	Silverstone (1) 
12051955	Hickory (1) 
Prestige	
12053046	Range Amber Beige (1)
12052734	Range Margaux Beige (2)
12052104	Range Chambord Grey (2)
12052365	Range Scandina Grey (1)
12052732	Rockland Black (1)
Standard	
12053045	Range Shaded Grey (2)
12052733	Range Newport Grey (2)

Sold in full cubes only

Can be double stacked

Production locations:

Metcalfe (1)

Milton (2)

C

C

B

B


B

A


A

A

Laying Patterns



Modular



Linear

Techniseal 1 bag of sand covers approx. 155 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 60 Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.