


Metrik™ Slab




	Dimensions mm	Dimensions in.
	60 x 70 x 280	2 3/8 x 2 3/4 x 11
Weight/unit	3 kg	6 lb
Area/unit	0.02 m ²	0.21 ft ²
Area/layer	0.92 m ²	9.95 ft ²
Area/cube	11.09 m²	12 Rows
Qty/cube	576 units	576 units
Weight/cube	1505 kg	3319 lb


Code	Colour
	Prestige
10502882	Rockland Black
127000940	Range Scandina Grey
Sold in full cubes only	
Can be double stacked	
Production location Milton	

Typical Row			


Laying Patterns




Checkerboard




Offset 1/2



Offset 1/3



Herringbone

 1 bag of sand covers approx. 55 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Metrik Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.