


Mondrian® Plus 80 Small Rectangle Paver




Pavers


	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	80 x 165 x 330	3 1/8 x 6 1/2 x 13		Prestige	
Weight/unit	10 kg	21 lb	10550516	Rockland Black	
Unit/area	18.52 units/m ²	1.71 units/ft ²	Sold in full cubes only		
Area/layer	0.82 m ²	8.79 ft ²	Production location Bolton		
Area/cube	7.38 m²	9 Rows			
Length/row	4.95 lin. m	16.25 lin. ft			
Length/cube	59.43 lin. m	195.00 lin. ft			
Qty/cube	135 units	135 units			
Weight/cube	1302 kg	2871 lb			



Laying Patterns



Linear



Herringbone

Techniseal 1 bag of sand covers approx. 29 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Mondrian Plus 80 Small Rectangle Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).