

# Trafalgar® 60 Paver




|   |                    | Dimensions mm              | Dimensions in.             |
|---|--------------------|----------------------------|----------------------------|
| A | A                  | 60 x 100 x 200             | 2 3/8 x 3 15/16 x 7 7/8    |
|   | B                  | 60 x 200 x 200             | 2 3/8 x 7 7/8 x 7 7/8      |
|   | C                  | 60 x 300 x 200             | 2 3/8 x 11 13/16 x 7 7/8   |
| B | Weight/unit (avg.) | 6 kg                       | 12 lb                      |
|   | Unit/area (avg.)   | 23.96 units/m <sup>2</sup> | 2.32 units/ft <sup>2</sup> |
|   | Area/layer         | 0.96 m <sup>2</sup>        | 11.63 ft <sup>2</sup>      |
| C | <b>Area/cube</b>   | <b>10.56 m<sup>2</sup></b> | <b>10 Rows</b>             |
|   | Qty/cube           | A = 80                     | B = 80                     |
|   | Length/row         | 5.40 lin. m                | 17.72 lin. ft              |
|   | Length/cube        | 54.01 lin. m               | 177.20 lin. ft             |
|   | Weight/cube        | 1441 kg                    | 3178 lb                    |

| Code                       | Colour              |
|----------------------------|---------------------|
|                            | <b>Prestige</b>     |
| 10550442                   | Range Margaux Beige |
|                            | <b>Standard</b>     |
| 10550368                   | Range Norvick Grey  |
| 10550370                   | Range Newport Grey  |
| Sold in full cubes only    |                     |
| Production location Milton |                     |


Typical Row

|   |   |   |   |   |   |
|---|---|---|---|---|---|
| A | A | A | A | A | A |
| B | C | C | A | A | B |
| C | C | C | C | C |   |
| B | B | B | B | B | B |
| C | C | C | C | C |   |

## Laying Patterns



Linear



Modular

**Techniseal** 1 bag of sand covers approx. 122 ft<sup>2</sup>

## TECHNICAL INFORMATION

| Product                   | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability                                        | Density | Absorption | Dimension Tolerance*                                                 |
|---------------------------|------------|-------------------|----------------------|------------------------------------------------------------------------------|---------|------------|----------------------------------------------------------------------|
| <b>Trafalgar 60 Paver</b> | CSA A231.2 | N/A               | μ 50 MPa<br>≥ 45 MPa | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

Runoff coefficient: 484 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).  
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).