


# Vendome® 60 and 80 Paver



**60 mm**  
Not  
vehicular




|                    | Dimensions mm              | Dimensions in.             |
|--------------------|----------------------------|----------------------------|
| A                  | 60 x 130 x 197             | 2 3/8 x 5 1/8 x 7 3/4      |
| B                  | 60 x 130 x 262             | 2 3/8 x 5 1/8 x 10 5/16    |
| C                  | 60 x 130 x 327             | 2 3/8 x 5 1/8 x 12 7/8     |
| Weight/unit (avg.) | 4 kg                       | 9 lb                       |
| Unit/area (avg.)   | 30.50 units/m <sup>2</sup> | 2.83 units/ft <sup>2</sup> |
| Area/layer         | 1.05 m <sup>2</sup>        | 11.28 ft <sup>2</sup>      |
| <b>Area/cube</b>   | <b>8.40 m<sup>2</sup></b>  | <b>8 Rows</b>              |
| Length/row         | 8.19 lin. m                | 26.87 lin. ft              |
| Length/cube        | 65.52 lin. m               | 214.96 lin. ft             |
| Weight/cube        | 1044 kg                    | 2302 lb                    |


| Code     | Colour              |
|----------|---------------------|
|          | <b>Prestige</b>     |
| 10554763 | Rockland Black      |
| 10554761 | Range Margaux Beige |
|          | <b>Standard</b>     |
| 10554762 | Range Newport Grey  |

Sold in full cubes only  
Production location Bolton

**Typical Row**



**80 mm**




|                    | Dimensions mm              | Dimensions in.             |
|--------------------|----------------------------|----------------------------|
| A                  | 80 x 130 x 197             | 3 1/8 x 5 1/8 x 7 3/4      |
| B                  | 80 x 130 x 262             | 3 1/8 x 5 1/8 x 10 5/16    |
| C                  | 80 x 130 x 327             | 3 1/8 x 5 1/8 x 12 7/8     |
| Weight/unit (avg.) | 5 kg                       | 12 lb                      |
| Unit/area (avg.)   | 30.50 units/m <sup>2</sup> | 2.83 units/ft <sup>2</sup> |
| Area/layer         | 1.05 m <sup>2</sup>        | 11.28 ft <sup>2</sup>      |
| <b>Area/cube</b>   | <b>8.40 m<sup>2</sup></b>  | <b>8 Rows</b>              |
| Qty/cube           | A = 88                     | B = 96                     |
| Length/row         | 7.86 lin. m                | 25.80 lin. ft              |
| Length/cube        | 62.90 lin. m               | 206.40 lin. ft             |
| Weight/cube        | 1382 kg                    | 3047 lb                    |


| Code     | Colour              |
|----------|---------------------|
|          | <b>Prestige</b>     |
| 10550002 | Rockland Black      |
| 10559011 | Range Margaux Beige |
|          | <b>Standard</b>     |
| 10559010 | Range Newport Grey  |

Sold in full cubes only  
Production location Bolton


**Typical Row**



## Laying Patterns



Linear



Modular

**Techniseal** 1 bag of sand covers approx. : Vendome 60 - 44 ft<sup>2</sup> / Vendome 80 - 33 ft<sup>2</sup>

## TECHNICAL INFORMATION

| Product              | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability                                        | Density | Absorption | Dimension Tolerance*                                                 |
|----------------------|------------|-------------------|----------------------|------------------------------------------------------------------------------|---------|------------|----------------------------------------------------------------------|
| <b>Vendome Paver</b> | CSA A231.2 | N/A               | μ 50 MPa<br>≥ 45 MPa | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

Runoff coefficient: 890 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).