



# Versailles® Slab




|                 | Dimensions mm       | Dimensions in.        |
|-----------------|---------------------|-----------------------|
|                 | 50 x 610 x 610      | 2 x 24 x 24           |
| Weight/unit     | 44 kg               | 97 lb                 |
| Unit/area       | 0.37 m <sup>2</sup> | 4.00 ft <sup>2</sup>  |
| Area/cube       | 7.43 m <sup>2</sup> | 80.00 ft <sup>2</sup> |
| <b>Qty/cube</b> | <b>20 units</b>     | <b>20 units</b>       |
| Weight/cube     | 880 kg              | 1940 lb               |

| Code                         | Colour       |
|------------------------------|--------------|
| 12059261                     | Alpine Grey  |
| 12059263                     | Trenton Grey |
| Production location Montreal |              |

## Typical Row



## Laying Pattern



Checkerboard

## TECHNICAL INFORMATION

| Product                | Standard   | Flexural Strength | Compressive Strength | De-icing salts freeze-thaw durability                                        | Density | Absorption | Dimension Tolerance*                                                 |
|------------------------|------------|-------------------|----------------------|------------------------------------------------------------------------------|---------|------------|----------------------------------------------------------------------|
| <b>Versailles Slab</b> | CSA A231.1 | ±4.5 MPa          | N/A                  | 225 g/m <sup>2</sup> after 28 cycles<br>500 g/m <sup>2</sup> after 49 cycles | N/A     | N/A        | Length: -1.0 to +2.0 mm<br>Width: -1.0 to +2.0 mm<br>Height: ±3.0 mm |

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.  
Compatible with pedestal systems.