


Vertex Paver



Light
Commercial




		Dimensions mm	Dimensions in.	Colour	Typical Row
A	A and B	100 x 150 and 300 x 600	4 x 5 7/8 and 11 13/16 x 23 5/8	White - Smooth	
	Unit/area	0.135 m ²	1.45 ft ²	Cinder Grey - Smooth	
	Area/cube	8.64 m²	92.88 ft²	Charcoal - Smooth	
B				Light Charcoal - Smooth	
	Weight/ft²	22.33 kg	49.13 lb	Black ETX - Smooth	
				Light Grey - Smooth	
				Beige Grey - Smooth	
				Beige - Smooth	
				Production location Montreal	


Laying Patterns



Diagonal 100 x 450
with Boulevard 300 pavers
100 x 450




False Curves
with Boulevard 300 pavers
150 x 150
with Boulevard 300 pavers
150 x 300




Insertions 300 x 600
with Boulevard 300 pavers
300 x 600




Garden 600 x 600
with Boulevard 300 pavers
600 x 600




Verde Lines
with Boulevard Verde pavers



Rows 150 x 450
with Boulevard 300 pavers
150 x 450



Side-by-side 150 and 300
with Boulevard 300 pavers
150 x 150
with Boulevard 300 pavers
150 x 300



Side-by-side 150 x 300
with Boulevard 300 pavers
150 x 300

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vertex Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.