



Vertex Slab




	Dimensions mm	Dimensions in.
A	60 x 200 and 302 x 610	2 3/8 x 7 7/8 and 11 7/8 x 24
B		
Weight/unit	39 kg	85 lb
Area/unit	0.153 m ²	1.65 ft ²
Area/layer	1.22 m ²	13.17 ft ²
Area/cube	12.2 m ² 10 Rows	131.7 ft ²
Qty/cube	80 units	80 units
Weight/cube	1725 kg	3803 lb

Code	Colour	Typical Row								
Prestige										
127001178	Range Amber Beige									
127001179	Range Scandinia Grey									
Sold in full cubes only										
Production location Quebec										
		<table><tr><td>A</td><td>B</td></tr><tr><td>A</td><td>B</td></tr><tr><td>B</td><td>A</td></tr><tr><td>B</td><td>A</td></tr></table>	A	B	A	B	B	A	B	A
A	B									
A	B									
B	A									
B	A									


Laying Patterns



Stack Bond



Arrows



Lines of Capio Paver



Rows with Melville 24 x 24 Slab

Techniseal 1 bag of sand covers approx. 181 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Vertex Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.