Wallstone® Wall







Standard



	Dimensions mm	Dimensions in.			
	100 x 200 x 300	3 15/16 x 7 7/8 x 11 13/16			
Weight/unit	13.3 kg	29.3 lb			
Unit/area	-	3.10 units/ft²			
Area/cube	-	34.80 ft ²			
Length/cube -		106.30 lin. ft			
Qty/cube	108 units	108 units			
Weight/cube	1436 kg	3165 lb			


CodeColourTypic16259322Desert Grey Blend

16259323 Granite Blend Sold by – 36 pieces

Split charges apply Production location Cambridge

Typical Row

Typical Row



Corner/ Column




	Dimensions mm	Dimensions in.			
	100 x 200 x 300	3 15/16 x 7 7/8 x 11 13/16			
Weight/unit	13.10 kg	28.90 lb			
Unit/area	-	0.54 ft ²			
Qty/cube	36 units	36 units			
Weight/cube	595 kg	1312 lb			


Code Colour 16259316 Desert Grey Blend 16259317 Granite Blend Sold by piece Split charges apply

Production location Cambridge

Laying Patterns



PATTERN 1: WALL ART 1 Place Wallstone standard units vertically and horizontally to create interesting patterns within the wall.



PATTERN 2: WALL ART 2

Add an additional dimension to your wall by including Wedgestone wall units in your pattern (shaded). Consider recessing blocks to add further distinction. Except for the coping course, it is not recommended to set units forward beyond the front of the base course.

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wallstone Wall	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Applications: Retaining walls MAX 10 m (3.3 ft)

Additional details: See our landscaping installation guide on our website.

Wallstone and Wedgestone Wall can be used seperately or in combination for greater flexibility.

Features: Suitable for gravity or grid, vertical or setback, straight or curved walls. All Wallstone Wall units come pre-split. End grooves on Wallstone Standard Units maintain interlock between courses, even when placed vertically. 2/3 of Standard Units are also double rock-faced.

Tips: Patterned Wallstone walls can be stacked vertically up to 6 courses high.



Wallstone 12 inch Capping










	Dimensions mm	Dimensions in.			
	100 x 200 x 300	3 15/16 x 7 7/8 x 11 13/16			
Weight/unit	13.10 kg	28.90 lb			
Units/length	-	3.1 units/ft²			
Length/row	-	106.30 lin. ft			
Qty/cube	108 units	108 units			
Weight/cube	1433 kg	3159 lb			

Code	Colour			
16259305	Desert Grey Blend			
16259306 Granite Blend				
Sold by 18 pieces Split charges apply Production location Cambridge				



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wallstone 12-inch Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm

Wedgestone Capping










	Dimensions mm	Dimensions in.			
	100 x 200 x 231 / 153	3 15/16 x 7 7/8 x 9 3/32 / 6			
Weight/unit	8.35 kg	18.40 lb			
Length/cube	-	113.60 lin. ft			
Qty/cube	150 units	150 units			
Weight/cube	1390 kg	3064 lb			

Code	Colour				
16259328	Desert Grey Blend				
16259329 Granite Blend					
Sold by 25 pieces Split charges apply					
Production location Cambridge					



TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wedgestone Capping	ASTM C 1372	N/A	20.7 MPa	N/A	2000 kg/m ²	10.4%	Length: ±3.2 mm Width: ±3.2 mm Height: ±3.2 mm