



Esbelto® DuraFusion Paver




	Dimensions mm		Dimensions in.		Code	Colour	Typical Row	
	80 x 305 x 610		3 1/8 x 12 x 24			DuraFusion		
	Weight/unit	37 kg	81 lb		127001989	Oasis - <i>91</i>		
	Unit/area	5.382 units/m²	0.50 unit/ft²		10551027	Marbella		
	Area/layer	1.11 m²	12.00 ft²		10551024	Silverstone		
	Area/cube	8.88 m²	8 Rows	96.00 ft²	10550536	Hickory		
	Length/layer	3.66 lin. m	12.00 lin. ft		Production location Metcalfe			
	Length/cube	29.26 lin. m	96.00 lin. ft					
	Qty/cube	48 units	48 units					
Weight/cube	1764 kg	3888 lb						


Laying Patterns




Checkerboard



Running Bond



Offset 1/3



Herringbone

1 bag of sand covers approx. 124 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Esbelto DuraFusion Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this Slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).