





Metrik™ Slab






	Dimensions mm	Dimensions in.	Code	Colour	Typical Row
	60 x 70 x 280	2 3/8 x 2 3/4 x 11		Prestige	
Weight/unit	3 kg	6 lb	10502882	Rockland Black	
Area/unit	0.02 m²	0.21 ft²	127000940	Range Scandina Grey	
Area/layer	0.92 m²	9.95 ft²	Can be double stacked		
Area/cube	11.09 m²	12 Rows	119.40 ft²		
Qty/cube	576 units	576 units	Production location St-Eustache		
Weight/cube	1505 kg	3319 lb			


Laying Patterns




Checkerboard



Offset 1/2



Offset 1/3



Herringbone

1 bag of sand covers approx. 55 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Metrik Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.