


Trafalgar® 60 Paver




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row			
A		A	60 x 100 x 200	2 3/8 x 3 15/16 x 7 7/8	10550442	Range Margaux Beige			
	B	60 x 200 x 200	2 3/8 x 7 7/8 x 7 7/8	Standard Range Norvick Grey Range Newport Grey					
	C	60 x 300 x 200	2 3/8 x 11 13/16 x 7 7/8						
B		Weight/unit (avg.)	6 kg			12 lb		10550368	Range Norvick Grey
	Unit/area (avg.)	23.96 units/m²	2.32 units/ft²			10550370		Range Newport Grey	
	Area/layer	0.96 m²	11.63 ft²			Production location Metcalfe			
C		Area/cube	10.56 m²			10 Rows		116.30 ft²	
	Qty/cube	A = 80	B = 80			C = 100			
	Length/row	5.40 lin. m	17.72 lin. ft						
	Length/cube	54.01 lin. m	177.20 lin. ft						
	Weight/cube	1441 kg	3178 lb						

Laying Patterns



Linear
0% Large Square



Modular
0% Large Square

Techniseal 1 bag of sand covers approx. 122 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Trafalgar 60 Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Runoff coefficient: 126 in per hour

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).