




Zen Paver




	Dimensions mm		Dimensions in.	Code	Colour	Typical Row 
		80 x 190 x 380	3 1/8 x 7 1/2 x 15		Prestige	
	Weight/unit (avg.)	12 kg	26 lb	10300745	Range Amber Beige	
	Unit/area (avg.)	18.04 units/m²	3.1 units/ft²	10301003	Range Scandina Grey	
	Area/layer	0.87 m²	9.33 ft²	Production location Montreal		
	Area/cube	7.83 m²	9 Rows	83.97 ft²		
	Qty/cube	108 units	108 units			
	Length/row	4.52 lin. m	14.84 lin. ft			
	Length/cube	40.72 lin. m	133.58 lin. ft			
	Weight/cube	1286 kg	2837 lb			

Laying Patterns



Linear



Linear

TECHNICAL INFORMATION

Product	Standard	Void Opening	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Zen Paver	CSA A231.2	27%	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Additional details: See our landscaping installation guide on our website (Permeable pavement section).