



# AquaPave<sup>®</sup> Paver



ASTM #8 Aggregate  
jointing material


Light  
Commercial



	Dimensions mm	Dimensions in.
	80 x 98 x 198	3 1/8 x 3 41/48 x 7
Weight/unit	3 kg	8 lb
Area/unit	0.42 m <sup>2</sup>	4.58 ft <sup>2</sup>
<b>Area/cube</b>	<b>8.77 m<sup>2</sup></b>	<b>94.40 ft<sup>2</sup></b>
Length/cube	132.60 lin. ft (rectangles only)	
Qty/cube	464 units (400 rectangles. 64 half-stone)	
Weight/cube	1608 kg	3545 lb
Packaged in herringbone to facilitate mechanical installation		

Code	Colour
10501969	Natural
Call for custom colour information	

## Laying Pattern



Running Bond

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
AquaPave Paver	CSA A231.2	N/A	µ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint spacing is 6 mm (0.24 in.) which allows an initial surface infiltration rate of +/- 3 018 mm/hr.

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.