## Boulevard TLI 150 Crescendo 320 Paver





	Colour
Г—Л	White - Smooth
=	Cinder Grey - Smooth
	Charcoal - Smooth
	Light Charcoal - Smooth
	Black ETX - Smooth
	Light Grey - Smooth
	Beige Grey - Smooth
	Beige - Smooth
	Red - Smooth

		(
		-
D D		
- En	222	
Ŧ	^^^	
ω.		

	Colour							
	Cinder Grey - Granitech							
	Light Charcoal - Granitech							
•	Charcoal - Granitech							
	Light Grey - Granitech							
	Beige Grey - Granitech							
	Beige - Granitech							
	Opal White - Granitech							
	Stanstead Grey - Granitech							
	Cambrian Brown - Granitech							
	Cambrian Black - Granitech							



smooth

	Dimensions mm	Dimensions in.
A	150 x 320 x 240	5 7/8 x 12 5/8 x 9 1/2
В	150 x 320 x 320	5 7/8 x 12 5/8 x 12 5/8
С	150 x 320 x 360	5 7/8 x 12 5/8 x 14 3/16
D	150 x 320 x 400	5 7/8 x 12 5/8 x 15 3/4
E	150 x 320 x 440	5 7/8 x 12 5/8 x 17 5/16
Cube ft <sup>2</sup>	49.6	12.4 per row
Cube ft <sup>2</sup>	49.6	12.4 per row
Cube ft <sup>2</sup>	37.2	1.4 per row

Mass/ft <sup>2</sup> Mass/ft <sup>2</sup>	32.6 kg 34.4 kg	71.7 lb
Mass/ft <sup>2</sup>	43.6 kg	95.9 lb

Typical	Row



## Laying Pattern

		I.	1		Ι.	
L L						
				L,		

Linear

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Boulevard TLI 150 Crescendo 320 Paver 125 x 500 250 x 500 500 x 500 750 x 500 200 x 200	CSA A231.2	N/A	µ 50 MPa ≥ 45 MPa	225 g/m² after 28 cycles 500 g/m² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene). Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards. Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.

## **PERMACON**