





City Slab



		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
		60 x 500 x 750	2 3/8 x 19 11/16 x 29 1/2		Prestige	
	Weight/unit	52 kg	114 lb	12051210	Cameo Beige	
	Area/unit	0.38 m²	4.04 ft²		Standard	
	Area/layer	0.75 m²	8.07ft²	12059437	Alpine Grey	
	Area/cube	9.00 m²	12 Rows	12059443	Sterling Grey	
	Qty/cube	24 units	24 units	Sold by layer		
	Weight/cube	1270 kg	2800 lb	Split charges apply		
			Production location St-Eustache			

Laying Patterns



Linear

1 bag of sand covers approx. 147 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
City Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.
Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this Slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).
This product can be installed on pedestals for a rooftop application. It can safely withstand a load of up to 300 kg.