



# Mega Melville® Slab




	Dimensions mm	Dimensions in.
	60 x 570 x 950	2 3/8 x 22 7/16 x 37 3/8
Weight/unit	76 kg	167 lb
Area/unit	0.54 m <sup>2</sup>	5.83 ft <sup>2</sup>
Area/layer	1.08 m <sup>2</sup>	11.56 ft <sup>2</sup>
<b>Area/cube</b>	<b>9.72 m<sup>2</sup></b>	<b>104.94 ft<sup>2</sup></b>
Qty/cube	18 units	18 units
Weight/cube	1364 kg	3007 lb


Code	Colour	Typical Row
<b>Prestige</b>		
127001794	Range Amber Beige (1)	
12052363	Range Margaux Beige (2)	
12052772	Range Chambord Grey (2)	
12052362	Range Scandina Grey (1)	
12052360	Rockland Black (2)	
<b>Standard</b>		
12053565	Range Shaded Grey (2)	
12052366	Range Newport Grey (2)	

Sold in full cubes only  
Production location:  
Metcalfe (1)  
Milton (2)

## Laying Patterns



Linear



Modular  
83% Melville 60  
17% Mega Melville 60

1 bag of sand covers approx. 289 ft<sup>2</sup>

## TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Mega Melville Slab</b>	CSA A231.1	±4.5 MPa	N/A	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this Slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).