



Melville® 80 and Melville® 80 DuraFusion Pavers




		Dimensions mm	Dimensions in.	Code	Colour	Typical Row
  	A	80 x 190 x 380	3 1/8 x 7 1/2 x 15		DuraFusion	
	B	80 x 380 x 380	3 1/8 x 15 x 15	127001988	Oasis - <i>91</i> (1)	
	C	80 x 380 x 570	3 1/8 x 15 x 22 7/16	10554893	Marbella (1)	
	Weight/unit (avg.)	25 kg	56 lb	10555066	Silverstone (1)	
	Unit/area (avg.)	7.39 units/m ²	0.69 unit/ft ²	10555067	Hickory (1)	
	Area/layer	1.08 m ²	11.66 ft ²		Prestige	
	Area/cube	8.64 m²	8 Rows 93.28 ft²	10550869	Range Amber Beige (1)	
	Length/row	3.04 lin. m	9.97 lin. ft	10550447	Range Margaux Beige (2)	
	Length/cube	24.32 lin. m	79.79 lin. ft	10554764	Range Chambord Grey (2)	
	Weight/cube	1625 kg	3583 lb	10550446	Range Scandina Grey (1)	
				10550557	Rockland Black (1)	
					Standard	
				10550868	Range Shaded Grey (2)	
				10550558	Range Newport Grey (2)	

Sold in full cubes only
Can be double stacked
Production locations:
Metcalf (1)
Milton (2)

Laying Patterns



Linear



Modular

1 bag of sand covers approx. 116 ft²

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Melville 80 and DuraFusion Paver	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Joint sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).
Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.